# OKIPOS 411

OKI
PRINTING SOLUTIONS

## The most innovative solution for POS and Retail

OKI introduces on point of sale market the new OKIPOS, very high speed thermal printer, up to 220mm/sec, quiet and with high performance.

OKIPOS represents a revolutionary printing solution for retail and hospitality market.

Reduced dimensions and winning design (many available colours), make OKIPOS easy to place inside point of sale where space need is priority.

OKIPOS can be vertical or horizontal mounted allowing to optimize working space and making it tidy thanks to hidden link cables.

Paper roll high capacity, 90mm diameter, allows to increase printing autonomy.

OKIPOS is able to print on 80mm or 82.5mm paper width.

The printer is completed with drivers (Window and Linux) and utility for logo and character creation and updating.

OKIPOS is available with serial RS232, USB, parallel and Ethernet interface and with cash drawer driver. OKIPOS is equipped with buzzer for sound signals, also polyphonics.

It is possible to customize different melodies linked to special events (receipt issue, last ticket, etc..).

This model is equipped with an internal printing server: friendly web pages allow you to monitor printer status, to set both printer working parameters and network configuration.

You can configure the email service to make maintenance and diagnostic operations easier.

A support area is available for downloading user manuals, printing drivers, software tools and furthermore to directly upgrade online the printer firmware!

# The OKIPOS 411 POS Printer

## OKIPOS 411 Specification

| | |
|---|---|
| **Printing method** | Thermal line printing |
| **Resolution** | 203dpi |
| **Printing speed (mm/sec)** | High Quality 140 Normal 180 High Speed 220 |
| **Character set** | PC437, PC850, PC860, PC863, PC865, PC858 (euro) |
| **Type styles** | Normal, 1x to 8x height and width, reverse, underscored, italic, bold |
| **Printing direction** | Straight, 90, 180, 270 |
| **Paper width** | 80mm / 82.5mm |
| **Roll dimension** | max Ø 90mm |
| **Emulation** | ESC/POS™ |
| **Interface** | RS232 / USB / Centronics / Ethernet |
| **Baud rate** | From 1.200 bps to 115.200 bps |
| **Data buffer** | 4 Kb |
| **Flash memory** | 384 Kb |
| **Graphic memory** | 2 logos of 608 x 862 dots |
| **Drivers** | Win95,98,me,2K,XP,NT4; Linux |
| **Software Tools** | Logo Editor, Font Editor |
| **Power consumption** | 3 A |
| **Power supply** | 24 Vdc ± 10% (external power supply) |
| **DKD function** | 1 driver |
| **Reliability MTBF** | 100 Km |
| **Safety** | EN60950 +A1+A2+A3+A4 |
| **Dimensions (WxDxH)** | 140x208x152 |
| **Weight** | 2 Kg |

*ESC/ POS™ is a registered trademark of Seiko Epson Corporation. Windows and Windows NT are registered trademarks of Microsoft . All Right Reserved.*
*All specifications are subject to change without notice.*

OKI
PRINTING SOLUTIONS

**OKI SYSTEMS(THAILAND) LTD.**
1168/81-82 Lumpini Tower, 27th Floor,
Rama IV Rd., Tungmahamek, Sathorn,
Bangkok 10120, Thailand
Tel : + 66 (0) 2679 - 9235-42
Fax : + 66 (0) 2679 - 9243, 45

www.okiprintingsolutions.com